

EINSTELLRINGE DIN 2250
SETTING RING GAUGES DIN 2250



- aus gehärtetem Lehenstahl und geläppt
- bis 200 mm DIN 2250 Form C
- Genauigkeit
bis 200 mm, DIN 286, JS 3
ab 225 mm, DIN 286, JS 4

- *hardened ground and lapped*
- *up to 200 mm DIN 2250 form C*
- *accuracy*
up to 200 mm, DIN 286, JS 3
from 225 mm, DIN 286, JS 4

Art.-Nr. <i>Item no.</i>	ø <i>mm</i>	Art.-Nr. <i>Item no.</i>	ø <i>mm</i>	Art.-Nr. <i>Item no.</i>	ø <i>mm</i>	Art.-Nr. <i>Item no.</i>	ø <i>mm</i>	Art.-Nr. <i>Item no.</i>	ø <i>mm</i>
313.003	3	313.021	21	313.045	45	313.090	90	313.165	165
313.003.5	3,5	313.022	22	313.046	46	313.092	92	313.170	170
313.004	4	313.023	23	313.047	47	313.095	95	313.175	175
313.004.5	4,5	313.024	24	313.048	48	313.098	98	313.180	180
313.005	5	313.025	25	313.050	50	313.100	100	313.185	185
313.006	6	313.026	26	313.052	52	313.105	105	313.187.5	187,5
313.007	7	313.027	27	313.055	55	313.110	110	313.190	190
313.008	8	313.028	28	313.058	58	313.112.5	112,5	313.195	195
313.009	9	313.029	29	313.060	60	313.115	115	313.200	200
313.010	10	313.030	30	313.062	62	313.120	120	313.225	225
313.011	11	313.032	32	313.065	65	313.125	125	313.250	250
313.012	12	313.033	33	313.068	68	313.130	130	313.275	275
313.013	13	313.034	34	313.070	70	313.135	135	313.300	300
313.014	14	313.035	35	313.072	72	313.137.5	137,5	313.325	325
313.015	15	313.036	36	313.075	75	313.140	140	313.350	350
313.016	16	313.037	37	313.078	78	313.145	145	313.400	400
313.017	17	313.038	38	313.080	80	313.150	150		
313.018	18	313.040	40	313.082	82	313.155	155		
313.019	19	313.042	42	313.085	85	313.160	160		
313.020	20	313.044	44	313.088	88	313.162.5	162,5		