

ULTRASCHALL-SONDE
ULTRASONIC PROBE



502.252



502.263



502.252



502.263

- Ultraschall-Sonde für 502.241 und 502.242
- *Ultrasonic probe for 502.241 and 502.242*

Art.-Nr. <i>Item no.</i>	Antrieb <i>Driver</i>	Messkraft <i>Meas. force</i>	Oszillationsstab <i>Oscillation Rod</i>	Abmessung (Kopf) <i>Dimension (head)</i>	Rauheit <i>Roughness</i>	Anforderungen an Prüfling <i>Requirement of probe</i>	
						Min. Gewicht <i>min. weight</i>	Min. Dicke <i>min. thickness</i>
502.251	manuell <i>manual</i>	10 N	ø 2,4 mm	154 x ø 22 ø 5,5	Ra < 2,5 µm	0,3 kg	2 mm
502.252	manuell <i>manual</i>	20 N	ø 2,4 mm	154 x ø 22 ø 5,5	Ra < 5 µm	0,3 kg	2 mm
502.253	manuell <i>manual</i>	50 N	ø 3 mm	154 x ø 22 ø 5,5	Ra < 10 µm	0,3 kg	2 mm
502.254	manuell <i>manual</i>	98 N	ø 3 mm	154 x ø 22 ø 5,5	Ra < 15 µm	0,3 kg	2 mm
502.261	motorisiert <i>motorized</i>	3 N	ø 3,7 mm	197,5 x ø 46 ø 36	Ra < 1 µm	0,3 kg	2 mm
502.262	motorisiert <i>motorized</i>	5 N	ø 3,7 mm	197,5 x ø 46 ø 36	Ra < 1,5 µm	0,3 kg	2 mm
502.263	motorisiert <i>motorized</i>	8 N	ø 3,7 mm	197,5 x ø 46 ø 36	Ra < 2 µm	0,3 kg	2 mm
502.264	motorisiert <i>motorized</i>	10 N	ø 3,7 mm	197,5 x ø 46 ø 36	Ra < 2,5 µm	0,3 kg	2 mm